

Technical Datasheet

CMB 116HS

1) Product Description:

- ✓ Product: White Master-Batch, Economical Grade
- ✓ Carrier: Poly Olefin
- ✓ Active Ingredients: Treated TiO₂ & Fine CaCO₃

2) Application & Addition Rate:

- ✓ PP Raffia Bag: 5 to 20%
- ✓ PE & PP Injection Molded Parts: 5 to 10% (depends on requirements)
- ✓ PP White Band: 5 to 20%

3) Advantages:

- ✓ Improve Stiffness & Modulus
- ✓ Enhance Dimensional Stability
- ✓ Reduce Shrinkage
- ✓ Improve Tensile Strength
- ✓ Replace Polymer and Reduce Cost
- ✓ Improve Heating/Cooling Rate, Reduce Cycle Time
- ✓ Act as Economical Grade White MB

4) Typical data:

PROPERTIES	TEST METHOD	UNIT	TYPICAL VALUE*
Melt Flow Rate (190°C/2,16 Kg)	ASTM D1238	gr/10min	8 ₊₂
Density	ASTM D 1505	g/cm ³	1.8
Moisture	ASTM D 644	%	Max 0.2

Address: No. 3, 12th Floor, A Block, Babak Plaza Building, Babak Ave, Baku, Azerbaijan

Tel: +994 124880752 | Email: mr.info@mrchemicalaz.com | www.mrchemicalaz.com