

Technical Datasheet

Lupolen 3026H

1) Product Description:

LDPE (Lupolen 3026H) is a non additivated, low density Polyethylene with high rigidity. It contains slip and anti-blocking agent. It is delivered in pellet form. The features are good Processability, Unspecified Slip, low Friction, good Stiffness

2) Applications:

- ✓ Bags and Pouches
- ✓ Film and Shrink film
- ✓ Cast and Blown film
- ✓ Food packaging Film
- ✓ Surface Protection Film

3) Processing method:

- ✓ Cast film
- ✓ Blown film

4) Typical data:

PROPERTIES	TEST METHOD	UNIT	TYPICAL VALUE*
Density	ISO 1183	g/cm ³	0.927
Melt Flow Rate (MFR) (190°C/2.16 Kg)	ISO 1133	g/10 min	2.0
Tensile Modulus	ISO 527-1, -2	MPa	300
Tensile Stress at Yield	ISO 527-1, -2	MPa	13.0
Tensile Strength MD/TD	ISO 527-1, -3	MPa	25/18
Tensile strain at break MD/TD	ISO 527-1, -3	%	350/600
Dart Drop Impact (50 blown film)	ASTM D 1709	g	110
Vicat Softening temp (A50(50° C/h 10N))	ISO 306	°C	100
Haze (50)	ASTM D 1003	%	<7.0
Gloss (60°, 50)	ASTM D 2457		>110

Address: No. 3, 12th Floor, A Block, Babak Plaza Building, Babak Ave, Baku, Azerbaijan

Tel: +994 124880752 | Email: mr.info@mrchemicalaz.com | www.mrchemicalaz.com