

## Technical Datasheet

WP526

### 1) General Information:

WP526, is one of the TPC Performance expandable polystyrene products range. It is a free flowing expandable polystyrene grade, consisting of spherical polystyrene beads containing pentane as the expansion agent.

Expandable polystyrene (EPS) is normally expanded to achieve the low densities required for final step expansion. The typical density of this grade is around 25 kg/m<sup>3</sup>, but other densities are possible depending on applications and equipment.

### 2) Applications:

✓ Shape Molding, Cups

Because of its small bead size WP526 is also used for very thin-wall water proof shape molding products such as drinking-cups.

### 3) Typical data:

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE*
BEAD SIZE	SUNPOR 7.2.5 (MIN 90% BY WT)	MM	(0.3-0.5)(>90%WT)
K-VALUE	SUNPOR 7.2.4	-	55
PENTANE CONTENT	SUNPOR 7.2.2	WT %	5.2%
EXPANDED DENSITY	SUNPOR 7.2.6	KG/M <sup>3</sup>	22-30
RESIDUAL MONOMER	SUNPOR 7.2.1	PPM	500

\* All above mentioned data are typical values and not to be construed as real specifications.

Address: No. 3, 12th Floor, A Block, Babak Plaza Building, Babak Ave, Baku, Azerbaijan

Tel: +994 124880752 | Email: [mr.info@mrchemicalaz.com](mailto:mr.info@mrchemicalaz.com) | [www.mrchemicalaz.com](http://www.mrchemicalaz.com)