

---

## Technical Datasheet

### GPPS1070

#### 1) Product Description:

GPPS1070 is a high molecular weight crystal polystyrene for special extrusion application with high mechanical properties.

#### 2) Applications:

- ✓ Insulation sheet
- ✓ Special extrusion

#### 3) Typical data:

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE*
Melt Flow Rate (200 °C, 5kg)	ASTM D-1238	g/10min	1.7
Styrene Residual Monomer	CLG LABPSG004 (ATOFINA TEST METHOD)	PPM	<500
Vicat softening point (50 °C/hr 1kg)	ASTM D-1525	°C	104
Tensile Strength at Break	ASTM D-638	MPA	57
Elongation at Break	ASTM D-638	%	3
Tensile Modulus	ASTM D-638	MPA	4710

\*All above mentioned data are typical values and not to be construed as real specifications.

Density and shrinkage of this grade are approximately around 1.04 kg/lit & (0.4-0.7)%(ASTM D-955) respectively. All test are carried out at 23°C , unless otherwise stated.

If the injection molding products quality is affected by moisture, granules of GPPS could be dried at 70°C for 2-4 hours.

---

Address: No. 3, 12th Floor, A Block, Babak Plaza Building, Babak Ave, Baku, Azerbaijan

Tel: +994 124880752 | Email: [mr.info@mrchemicalaz.com](mailto:mr.info@mrchemicalaz.com) | [www.mrchemicalaz.com](http://www.mrchemicalaz.com)