
Technical Datasheet

E7544

1) Specification:

- ✓ The E-PVC Emulsion-Paste grade

2) Applications:

- ✓ Leather Skin, Metal Coating, Molding, Wall Covering, Gloves, Marking Films

3) Typical data:

| PARAMETER | TEST METHOD | | TYPICAL VALUE |
|---------------------------------|-------------------|--------------|---------------|
| K-Value | ISO 1628/2 | DIN 53726 | 74-76 |
| Sieve analysis $\geq 63\mu$ (%) | ISO 565 | DIN 53724 | 1.5 \geq |
| Volatile matter (%) | ISO 1269 | DIN 7764/2 | 0.3 \geq |
| Methanol extract (%) | ISO 6427 | DIN 53738 | 2.5 \geq |
| Residual VCM (ppm) | ISO 6401 | DIN 53743 | 1 \geq |
| Thermostability (min) | Vinnolit THMA 180 | | 20 \leq |
| Paste Viscosity | ISO 3219 | DIN EN 11468 | 5 \geq |

Address: No. 3, 12th Floor, A Block, Babak Plaza Building, Babak Ave, Baku, Azerbaijan

Tel: +994 124880752 | Email: mr.info@mrchemicalaz.com | www.mrchemicalaz.com